

# ZD410 Direct Thermal Printer

## ULTRA-COMPACT AND FAST “FITS ANYWHERE” 2-INCH PRINTER

If you need fast, dependable printing in the most space constrained areas, you need the ZD410. This ultra-compact “fits anywhere” printer is designed for the smallest of work spaces. When it comes to flexibility, the ZD410 shines — this printer creates high-quality labels, receipts, tags and wristbands. This super-fast printer keeps your workers productive. Deployment is a breeze — the ZD410 is loaded with connectivity options. The ZD410 is easy to use, operate and troubleshoot, ensuring your printer is always up and running. And Zebra OneCare service maximizes the availability and productivity of your ZD410 printers with unmatched from-the-manufacturer support that covers everything — from worn out printheads to normal wear and tear. The ZD410 — the little printer designed with big business functionality.



### Ultra compact “fits anywhere” printer

The ZD410 is the smallest printer in its class, fitting easily in the most space-constrained desktop or shelf — you can even mount it on a wall.

### Adaptable to meet your current and future needs

The movable media sensor supports media with off-center black marks, die-cut notches or multiple labels across the width. Easily deploy in practically any technology environment with virtually every modern connectivity option, including USB, auto-sensing serial or 10/100 Ethernet and the latest wireless options — 802.11ac Wi-Fi and Bluetooth 4.1. You can support Wi-Fi and Ethernet connectivity simultaneously. Add new communication or media handling options in the future, such as serial or Ethernet connectivity, and a peeler and a cutter, right on site. Backwards compatibility with existing applications, formats and printer languages allows you to easily upgrade from your aging Zebra LP 2824 Plus — just

plug in the ZD410 and you’re back up and running. And with support for Zebra ZPL and EPL printer languages and many non-Zebra languages, it’s easy to upgrade from competitive printers.

### Easy to use and troubleshoot

Five status icons — status, pause, data, supplies and network — provide the additional information you need to keep your Zebra printer up, running and available. Now, at glance, users can see if the media needs to be replenished, if the network connection is down and much more.

### Easy to clean and sanitize healthcare model

Disinfectant-ready plastics and a sealed button interface make it easy to clean and disinfect the ZD410 healthcare model — crucial in hospitals and clinics. And with the 300 dpi printing option, even the small labels on specimen containers and prescriptions are highly legible.

### Link-OS for unparalleled ease of management

Zebra’s Link-OS unique printer software platform makes it easier than ever to integrate, manage and maintain one printer, a group of specific printers or all printers anywhere in the world via the cloud. And a quick tap of an NFC-enabled mobile device on the ZD410 provides access to Zebra’s extensive knowledge base of how-to videos and more for fast issue resolution.

### Optional battery for cordless operation

With the removable desktop battery power option, you can easily transport the ZD410 printer on a cart to enable on-the-spot printing to reduce steps, increase productivity and improve task accuracy. The battery housing mounts securely to the printer base and connecting the battery is as simple as snapping the battery into the housing. And the high-capacity battery can power it all for a full shift — the printer at maximum print speed, along with a peeler, cutter and keyboard.



**THE ZD410 — THE LITTLE PRINTER DESIGNED WITH BIG BUSINESS FUNCTIONALITY.**

For more information, visit [www.zebra.com/zd410](http://www.zebra.com/zd410)

# ZD410 Specifications Chart

## STANDARD FEATURES

- Direct Thermal print method
- ZPL and EPL programming languages
- 5 status icon, 3 button user interface
- USB 2.0, USB Host
- Bluetooth low energy
- OpenACCESS™ for easy media loading
- Dual-wall frame construction
- ENERGY STAR qualified

## PHYSICAL CHARACTERISTICS

<b>Dimensions</b>	8.6 in. L x 4.5 in. W x 6.0 in. H 220 mm L x 115 mm W x 151 mm H
<b>Weight</b>	2.2 lbs./1.0 kg

## PRINTER SPECIFICATIONS

<b>Resolution</b>	203 dpi/8 dots per mm Optional 300 dpi/12 dots per mm
<b>Memory</b>	512 MB Flash; 256 MB SDRAM
<b>Maximum Print Width</b>	2.2 in./56 mm for 203 dpi and 300 dpi
<b>Maximum Print Speed</b>	6 in./152 mm per second (203 dpi) 4 in./102 mm per second (300 dpi)
<b>Media Sensors</b>	Full width, moveable reflective/black mark sensor; multi-position transmissive/ gap sensor
<b>Firmware</b>	ZPL II; EPL 2; EPL Line Mode; XML; ZBI

## MEDIA CHARACTERISTICS

<b>Maximum Label Length</b>	39.0 in./991 mm
<b>Maximum Label and Media Width</b>	2.36 in./60 mm
<b>Media Roll Size</b>	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7mm) and 1.0 in. (25.4mm) standard, 1.5 in. (38.1), 2.0 in., (50.8mm) and 3.0 in. (76.2mm) using optional adapters
<b>Thickness</b>	0.003 in. (0.08 mm) min. - 0.0075 (.1905mm)
<b>Media Types</b>	Roll-fed or fan-fold, die cut or continuous direct thermal labels with or without black mark, tag stock, continuous receipt paper, and wristbands

## OPERATING CHARACTERISTICS

<b>Operating Temp.</b>	40° to 105° F/4.4° to 41° C
<b>Storage Temp.</b>	-40° to 140° F/-40° to 60° C
<b>Operating Humidity</b>	10% to 90% non-condensing
<b>Storage Humidity</b>	5% to 95% non-condensing
<b>Electrical</b>	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified; optional 2750 mAh battery

## PRINTER SUPPLIES

Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.

## OPTIONS AND ACCESSORIES

<b>Media Handling</b>	Field installable dispenser — label peel and present with label present sensor; field installable cutter
<b>Communications</b>	Field installable RS-232 auto-sensing Serial, DB-9; Factory installed or field installable Ethernet — 10/100 internal; factory installed wireless dual radio: 802.11ac Wi-Fi and Bluetooth 4.1; Bluetooth Low Energy included as standard on network connected models
<b>Battery</b>	Provides power to the printer to support a full shift of printing at maximum print speed; supports all media handling options
<b>Healthcare Model</b>	Healthcare model with IEC 60601-1 compliant power supply and healthcare wipeable plastics
<b>Real Time Clock</b>	Real time clock included as standard on network connected models
<b>Keyboard Display Unit</b>	ZKDU keyboard display units for stand-alone printing solutions
<b>Mounting Plate</b>	Optional accessory to secure ZD Series printers to countertops or shelves

## FONTS/GRAPHICS/SYMBOLOGIES

<b>Barcode Ratios</b>	2:1 and 3:1
<b>1D Barcodes</b>	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
<b>2D Barcodes</b>	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
<b>Fonts and Graphics</b>	16 resident expandable ZPL II bitmap fonts, two resident scalable ZPL fonts, five resident expandable EPL2 fonts, native open-type font support, Unicode compliant. China units include SimSun simplified Chinese font 64 MB user available non-volatile memory, 8 MB user available SDRAM

## REGULATORY

IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus  
CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

## PRINT DNA

This printer is supported by our powerful Print DNA suite of applications, utilities and developer tools that give our printers better performance, simplified remote manageability, and easier integration. Print DNA features may vary by model and may require a Support Contract. For more information, please visit [www.zebra.com/printdna](http://www.zebra.com/printdna)

## RECOMMENDED SERVICES

Zebra OneCare Select

The ZD410 is ideal in space-constrained areas for many applications, including:

### Retail

- Return tags
- Shelf labeling
- Price markdowns
- Prescription labeling
- Coupon printing

### Healthcare

- Prescription labels
- Patient record labels
- Lab and specimen labeling
- Patient ID wristbands

### Transportation & Logistics

- Routing labels
- Asset tracking tags

### Manufacturing (light industrial)

- Work-in-process labeling
- Product labeling

### Security

- Visitor ID
- Evidence tracking

### Travel and Hospitality

- Ticketing
- Luggage/bag tags



NA and Corporate Headquarters  
+1 800 423 0442  
inquiry4@zebra.com

Asia-Pacific Headquarters  
+65 6858 0722  
contact.apac@zebra.com

EMEA Headquarters  
zebra.com/locations  
contact.emea@zebra.com

Latin America Headquarters  
+1 847 955 2283  
la.contactme@zebra.com